



WALL

CLASSIC

COLOR WHEEL™ COLLECTION – GLAZED CERAMIC



 daltile®  
IMAGINE WHAT'S POSSIBLE™



# CLASSIC

COLOR WHEEL™ COLLECTION – GLAZED CERAMIC

## A Spectacular Spectrum

The element of color is visually represented in Color Wheel™. This vibrant collection offers a wide spectrum of colorful selections from bright and pigmented hues to neutral and earthy tones. A favorite of artists and designers, Color Wheel provides the perfect palette to inspire the imagination.

### • COLOR SCHEME

- Eighteen rich semi-gloss colorful accents
- Plus, twelve coordinating neutral tones in semi-gloss and matte finishes

### • ARTISTIC INSPIRATIONS

- Stylish shapes in classic size options
- With endless design opportunities, this collection is a perfect fit for residential and commercial applications



Cover photo features Color Wheel™ Classic Ocean Blue, Galaxy, & Desert Grey 6 x 6 on the wall with Emerson Wood™ Brazilian Walnut 8 x 48 on the floor. Above photo features Color Wheel™ Classic Artic White & Navy on the walls.

### WALL

### USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



C-G  
CRACK GUARANTEE



LOW HIGH

SEE CHARTS FOR FULL PRODUCT DETAILS

SPECIAL FEATURES




## SIZES:




6 x 6  
Wall Tile4 x 4  
Wall Tile3 x 6  
Wall Tile3 x 6  
Bevel Wall Tile

FINISHES: MATTE | SEMI-GLOSS




## SEMI-GLOSS

WHITE  
0100 (1)ARCTIC WHITE  
0190 (1)BISCUIT  
K175 (1)ALMOND  
0135 (1)URBAN PUTTY  
0161 (2)ARCHITECTURAL  
GRAY 0109 (2)ELEMENTAL TAN  
0166 (2)ARTISAN BROWN  
0144 (2)DESERT GRAY  
X114 (1)SUEDE GRAY  
0182 (2)CHALKBOARD  
0180 (2)BLACK  
K111 (2)

## MATTE

MATTE ARCTIC WHITE  
0790 (1)MATTE BISCUIT  
K775 (1)MATTE ALMOND  
X735 (1)MATTE URBAN PUTTY  
0761 (2)MATTE ARCHITECTURAL  
GRAY 0709 (2)MATTE ELEMENTAL  
TAN 0766 (2)MATTE ARTISAN  
BROWN 0744 (2)MATTE DESERT  
GRAY X714 (1)MATTE SUEDE GRAY  
0782 (2)MATTE CHALKBOARD  
0780 (2)MATTE BLACK  
K711 (2)

## ACCENT\*

CORNSILK  
0160 (3)MUSTARD  
1012 (3)SUNFLOWER  
DH50 (3)ORANGE BURST  
1097 (3)CURRANT  
SH17 (3)PLUM CRAZY  
1178 (3)SPA  
0148 (3)GARDEN SPOT  
0141 (3)KEY LIME  
1098 (3)ELECTRIC BLUE  
1194 (3)COBALT  
DM14 (3)\*WOOD VIOLET  
1467 (3)WATERFALL  
0169 (3)EMERALD  
0115 (3)OCEAN BLUE  
1049 (3)SEA BREEZE  
1174 (3)GALAXY  
1469 (3)NAVY  
K189 (3)

\* Accent available in Semi-Gloss finish only. † Subject to crazing; black grout not recommended  
(1), (2) and (3) indicate price groups. (1) being the least expensive.



STAINPROOF



DENTPROOF

SCRATCH-RESISTANT\*  
\*Applicable to products with Matte and Textured FinishesFIRE-RESISTANT\*  
\*Not Applicable to Heat-Mounted Mosaics

SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT [WWW.DAL TILE.COM](http://WWW.DAL TILE.COM) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

CLASSIC




COLOR WHEEL™ COLLECTION – GLAZED CERAMIC



TRIM

			Thickness	Pieces/ Carton
TRIM				
	S1/212J / 1/2 x 12 Jolly	(1/2" x 11-15/16") (1.29 cm x 30.36 cm)	1/4" 7.23 mm	12
	A106 / 1 x 6 Quarter Round	(1" x 6") (2.43 cm x 15.16 cm)	5/16" 7.90 mm	152
	AC106 / 1 x 6 Quarter Round Corner	(1" x 6") (2.43 cm x 15.16 cm)	5/16" 7.90 mm	120
SURFACE BULLNOSE				
	S4269 / 2 x 6 Bullnose	(2" x 6") (5.15 cm x 15.31 cm)	5/16" 7.90 mm	100
	SN4269 / 2 x 2 Bullnose Corner	(2" x 2") (5.15 cm x 5.15 cm)	5/16" 7.90 mm	25
	S4669 / 6 x 6 Bullnose	(6" x 6") (15.31 cm x 15.31 cm)	5/16" 7.90 mm	50
	SCRL4669 / 6 x 6 Bullnose Corner	(6" x 6") (15.31 cm x 15.31 cm)	5/16" 7.90 mm	50
	S4449 / 4 x 4 Bullnose	(4-1/4" x 4-1/4") (10.90 cm x 10.90 cm)	5/16" 7.90 mm	100
	SCRL4449 / 4 x 4 Bullnose Corner	(4-1/4" x 4-1/4") (10.90 cm x 10.90 cm)	5/16" 7.90 mm	100
	S4369MOD / 3 x 6 Bullnose (on 6" side)	(3" x 6") (7.65 cm x 15.31 cm)	5/16" 7.90 mm	100
	S4639MOD / 3 x 6 Bullnose (on 3" side)	(3" x 6") (7.65 cm x 15.31 cm)	5/16" 7.90 mm	100
	SCR4369M / 3 x 6 Bullnose Corner Right	(3" x 6") (7.65 cm x 15.31 cm)	5/16" 7.90 mm	100
	SCL4369M / 3 x 6 Bullnose Corner Left	(3" x 6") (7.65 cm x 15.31 cm)	5/16" 7.90 mm	100
RADIUS BULLNOSE				
	A4200 / 2 x 6 Bullnose	(2" x 6") (5.28 cm x 15.20 cm)	5/16" 7.90 mm	100
	AN4200 / 2 x 2 Bullnose Corner	(2" x 2") (5.28 cm x 5.28 cm)	5/16" 7.90 mm	20
FLAT TOP COVE BASE ^				
	A3601 / 6 x 6 Cove Base	(6" x 6") (15.31 cm x 15.31 cm)	5/16" 7.90 mm	44
	SCR3601 / 6 x 6 Cove Corner Right	(6" x 6") (15.31 cm x 15.31 cm)	5/16" 7.90 mm	20
	SCL3601 / 6 x 6 Cove Corner Left	(6" x 6") (15.31 cm x 15.31 cm)	5/16" 7.90 mm	20
	A3401 / 4 x 4 Cove Base	(4-1/4" x 4-1/4") (10.90 cm x 10.90 cm)	5/16" 7.90 mm	84
	SCR3401 / 4 x 4 Cove Corner Right	(4-1/4" x 4-1/4") (10.90 cm x 10.90 cm)	5/16" 7.90 mm	30
	SCL3401 / 4 x 4 Cove Corner Left	(4-1/4" x 4-1/4") (10.90 cm x 10.90 cm)	5/16" 7.90 mm	30
	A3361MOD / 3 x 6 Cove Base	(3" x 6") (7.65 cm x 15.31 cm)	5/16" 7.90 mm	36
	SCR3361M / 3 x 6 Cove Base Corner Right	(3" x 6") (7.65 cm x 15.31 cm)	5/16" 7.90 mm	36
	SCL3361M / 3 x 6 Cove Base Corner Left	(3" x 6") (7.65 cm x 15.31 cm)	5/16" 7.90 mm	36
SANITARY COVE BASE ^				
	S3619T / 6 x 6 Cove Base	(6" x 6") (15.31 cm x 15.31 cm)	5/16" 7.90 mm	40
	SCR3619T / 6 x 6 Cove Base Corner Right	(6" x 6") (15.31 cm x 15.31 cm)	5/16" 7.90 mm	20

TRIM (CON'T)

			Thickness	Pieces/ Carton
	SCL3619T / 6 x 6 Cove Base Corner Left	(6" x 6") (15.31 cm x 15.31 cm)	5/16" 7.90 mm	20
	S3419T / 4 x 6 Cove Base	(4-1/4" x 6") (10.90 cm x 15.31 cm)	5/16" 7.90 mm	60
	SCR3419T / 4 x 6 Cove Base Corner Right	(4-1/4" x 6") (10.90 cm x 15.29 cm)	5/16" 7.90 mm	20
	SCL3419T / 4 x 6 Cove Base Corner Left	(4-1/4" x 6") (10.90 cm x 15.31 cm)	5/16" 7.90 mm	20
SANITARY COVE BASE - Slim Foot Design *				
	S3619TN / 6 x 6 Cove Base	(6" x 6") (15.31 cm x 15.31 cm)	5/16" 7.90 mm	40
	SC3619TN / 1 x 6 Cove Base Corner	(1" x 6") (2.43 cm x 15.16 cm)	5/16" 7.90 mm	60





- ▲ Available in Group 1 & 2 Colors. Group 3 Colors are Made-to-Order.
- ★ Available in Group 1 Colors. Group 2 & 3 Colors are Made-to-Order.

TRIM USAGE

Wall Tile	6 x 6	4 x 4	3 x 6	3 x 6 Bevel
Jolly	S1/212J	S1/212J	S1/212J	S1/212J
Quarter Round	A106	A106	A106	A106
Quarter Round Corner	AC106	AC106	AC106	AC106
SURFACE BULLNOSE				
Bullnose	S4669	S4449	S4369MOD & S4639MOD	
Corner	SCRL4669	SCRL4449	SCR4369M & SCL4369M	
Bullnose	S4269	S4269	S4269	
Corner	SN4269	SN4269	SN4269	SN4269
RADIUS BULLNOSE				
Bullnose	A4200	A4200	A4200	
Corner	AN4200	AN4200	AN4200	
FLAT TOP COVE BASE				
Cove Base	A3601	A3401	A3361MOD	A3361MOD
Cove Base Corner	SCR3601 & SCL3601	SCR3401 & SCL3401	SCR3361M & SCL3361M	SCR3361M & SCL3361M
	Best Match			



## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	6 x 6 Wall Tile	(6" x 6") (15.31 cm x 15.31 cm)	5/16" 7.90 mm	12.50	50
	4 x 4 Wall Tile	(4-1/4" x 4-1/4") (10.90 cm x 10.90 cm)	5/16" 7.90 mm	12.50	100
	3 x 6 Wall Tile	(3" x 6") (7.65 cm x 15.31 cm)	5/16" 7.90 mm	12.50	100
	3 x 6 † Bevel Wall Tile	(3" x 6") (7.65 cm x 15.31 cm)	3/8" 9.40 mm	10.40	80

† Bevel is available in Group 1 colors only.

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓*
Pool Linings	N/A	✓


A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).

## APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

\* Matte finishes only. No Bevel Tile. Darker colors may show scratches.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
Wall: 1/16"	 Low (V1)

## PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20.0%
Breaking Strength	C648	120-230 lbs
Scratch Hardness	MOHS	4.0-6.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: [daltile.com/information/TestResults](http://daltile.com/information/TestResults).

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: [daltile.com/Factors](http://daltile.com/Factors).

## LRV &amp; MUNSELL

Color #	LRV Illuminate-OBS: F02-02 (CWF)	Munsell
SEMI-GLOSS		
0100	83.9	2.6Y 9.2/0.5
0190	83.9	7.0Y 9.2/0.2
K175	75.9	5.2Y 8.8/0.9
0135	68.0	2.9Y 8.4/1.2
0161	48.0	1.7Y 7.3/1.5
0166	26.8	1.1Y 5.7/1.6
0144	14.5	5.9YR 4.3/1.3
0109	37.9	6.0Y 6.6/1.0
X114	43.7	1.4GY 7.0/0.3
0182	22.6	1.9B 5.3/0.1
0180	11.4	1.3B 3.9/0.4
K111	5.0	10.0B 2.6/0.1
MATTE		
0790	83.4	4.9Y 9.2/0.2
K775	75.9	5.2Y 8.8/0.9
X735	70.9	3.5Y 8.6/1.2
0761	48.1	2.5Y 7.3/1.5
0766	26.8	0.2Y 5.7/1.7
0744	13.9	7.6YR 4.3/1.3
0709	36.9	5.6Y 6.5/1.0
X714	43.9	3.6GY 7.0/0.4
0782	22.3	9.8G 5.3/0.1
0780	11.1	0.6B 3.9/0.4
K711	5.8	3.3PB 2.8/0.1
ACCENT		
K189	5.9	5.0PB 2.9/1.2
1012	48.1	9.7YR 7.2/6.9
1049	18.0	1.9B 5.0/4.5
1097	26.4	10.1R 5.6/10.2
0115	11.7	3.3G 4.1/4.9
1174	9.1	5.8PB 3.6/5.6
1178	6.8	5.9RP 3.1/2.0
SH17	14.0	5.1R 4.4/11.1
0141	24.7	3.0GY 5.5/2.1
0148	48.3	3.7BG 7.4/1.3
0160	73.3	3.3Y 8.7/3.3
0169	40.4	9.7B 6.9/2.6
1469	9.3	4.5PB 3.6/2.7
DH50	70.6	4.7Y 8.4/8.8
DM14	4.7	9.9PB 2.5/4.4
1098	50.9	2.6GY 7.4/5.2
1194	19.0	0.3PB 5.2/6.7
1467	16.6	7.0P 4.6/2.2

 POST-CONSUMER  
RECYCLED MATERIALS

 PRE-CONSUMER  
RECYCLED MATERIALS

 MADE IN THE U.S.A.

All or select items within this series meet the requirements for these qualifications. For more information, visit [daltile.com](http://daltile.com).





MOSAIC

# COLOR WHEEL™ MOSAICS

GLAZED CERAMIC



 daltile®  
IMAGINE WHAT'S POSSIBLE™



# COLOR WHEEL™ MOSAICS

GLAZED CERAMIC

## A Spectacular Spectrum


The element of color is visually represented in Color Wheel™. This vibrant collection offers a wide spectrum of colorful selections from bright and pigmented hues to neutral and earthy tones. A favorite of artists and designers, Color Wheel provides the perfect palette to inspire the imagination.

### • COLOR SCHEME

- Eight rich semi-gloss colorful accents
- Plus, eight coordinating neutral tones in semi-gloss and matte finishes

### • ARTISTIC INSPIRATIONS

- Stylish shapes from unique linear sizes to exciting mosaic designs
- With endless design opportunities, this collection is a perfect fit for residential and commercial applications



Cover photo features Color Wheel™ Mosaics Matte Arctic White 1 x 6 mosaic on the wall, Ocean Blue & Matte Arctic White 1.5" Hexagon mosaic on the right wall, Matte Arctic White Penny Round mosaic on the shower floor and Gamma™ Hypnotic 12 x 24 matte on the floor.

Above photo features Color Wheel™ Mosaics Mustard, Orange Burst, Currant & Arctic White Penny Round mosaics on the fountain and Keystones™ Matte Arctic White 2 x 2 mosaic in the pool.

### MOSAIC

#### USAGE



SEE CHARTS FOR FULL PRODUCT DETAILS

### SPECIAL FEATURES







## SIZES:

2 x 2  
Mosaic1.5" Hexagon  
Mosaic1.5" Arctic  
White & Black  
Hexagon  
Mosaic\*1 x 6  
Mosaic1 x 3  
Herringbone  
Mosaic1 x 3 Lattice  
Weave MosaicPenny Round  
Mosaic




FINISHES: SEMI-GLOSS | MATTE

## SEMI-GLOSS

BLACK  
K111 (2)ARCTIC WHITE  
0190 (1)BISCUIT  
K175 (1)URBAN PUTTY  
0161 (2)ARCHITECTURAL  
GRAY 0109 (2)DESERT GRAY  
X114 (1)SUEDE GRAY  
0182 (2)CHALKBOARD  
0180 (2)ARCTIC WHITE  
WITH BLACK PENNY  
ROUND MOSAIC

CW50 GLOSS

## MATTE




MATTE BLACK  
K711 (2)MATTE ARCTIC  
WHITE 0790 (1)MATTE BISCUIT  
K775 (1)MATTE URBAN  
PUTTY 0761 (2)MATTE  
ARCHITECTURAL  
GRAY 0709 (2)MATTE DESERT  
GRAY X714 (1)MATTE SUEDE  
GRAY 0782 (2)MATTE  
CHALKBOARD  
0780 (2)MATTE ARCTIC  
WHITE WITH MATTE  
BLACK PENNY  
ROUND MOSAIC

CW51 MATTE

## ACCENT+

MUSTARD  
1012 (3)ORANGE BURST  
1097 (3)CURRANT  
SH17 (3)EMERALD  
0115 (3)SEA BREEZE  
1174 (3)OCEAN BLUE  
1049 (3)NAVY  
K189 (3)PLUM CRAZY  
1178 (3)

## SIZES

2 x 2 MOSAIC  
(DOT-MOUNTED ON  
12" x 24" SHEET)1 x 6 MOSAIC  
(DOT-MOUNTED ON  
10" x 12" SHEET)1.5" HEXAGON MOSAIC  
(DOT-MOUNTED ON  
12" x 11" SHEET)1 x 3 HERRINGBONE  
MOSAIC  
(DOT-MOUNTED ON  
9" x 12" SHEET)1.5" ARCTIC WHITE  
WITH BLACK HEXAGON  
MOSAIC\* CW50 GLOSS  
AND CW51 MATTE  
(MESH-MOUNTED ON  
14" x 12" SHEET)PENNY ROUND  
MOSAIC\*  
(DOT-MOUNTED ON  
13" x 13" SHEET)1 x 3 LATTICE WEAVE  
MOSAIC  
(DOT-MOUNTED ON  
12 x 12 SHEET)

+ Accent available in Semi-Gloss finish only.

(1), (2) and (3) indicate price groups. (1) being the least expensive.

Shapes stocked in all colors. Blends and patterns are also available on a made to order basis.

\* Stocked in all colors and patterns (CW50 Gloss and CW51 Matte).

Other pattern and blend options available (in any size, color or finish) on a made to order basis.



SLIP RESISTANT



STAINPROOF



DENTPROOF

SCRATCH-RESISTANT™  
\*Applicable to products with Matte and  
Textured FinishesFIRE-RESISTANT™  
\*Not Applicable to Mesh-Mounted  
Mosaics

CLIMATEPRO™



SIMPLICLEAN™








VISIT THE WHY TILE PAGE AT [WWW.DAL TILE.COM](http://WWW.DAL TILE.COM) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

# COLOR WHEEL™ MOSAICS

GLAZED CERAMIC



## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	2 x 2 Mosaic (Dot-mounted on 12" x 24" Sheet)	(12" x 24" Sheet) (30.48 cm x 60.96 cm Sheet)	1/4" (6 mm)	24.00	12
	1 x 6 Mosaic (Dot-mounted)	(9-3/4" x 11-1/2" Sheet) (24.76 cm x 29.21 cm Sheet)	5/16" (8 mm)	8.30	10
	1.5" Hexagon Mosaic (Dot-mounted on 12" x 11" Sheet)	(11-5/8" x 10-1/4" Sheet) (28.89 cm x 26.04 cm Sheet)	1/4" (6 mm)	9.72	12
	1.5" White & Black Hexagon Mosaic (Mesh-mounted on 14" x 12" Sheet)	(14" x 11-1/2" Sheet) (35.56 cm x 29.21 cm Sheet)	1/4" (6 mm)	10.00	10
	1 x 3 Herringbone Mosaic (Dot-mounted )	(9" x 12" Sheet) (22.86 cm x 30.48 cm Sheet)	1/4" (6 mm)	6.00	10
	3/4" Penny Round Mosaic♦ (Dot-mounted)	(11-3/8" x 13-3/8" Sheet) (28.89 cm x 33.97 cm Sheet)	1/4" (6 mm)	10.60	10
	1 x 3 Lattice Weave Mosaic (Dot-mounted)	(12" x 12" Sheet) (30.48 cm x 30.48 cm Sheet)	1/4" (6 mm)	10.00	10


\* Stocked in Arctic White with Black (both CW50 gloss and CW51 matte).  
Other pattern options available on a made to order basis.

♦ Penny Round mosaics are stocked in all colors and in  
CW50 Gloss & CW51 Matte Arctic White with Black patterns.

## LRV & MUNSELL

Color #	LRV Illuminate-OBS: F02-02 (CWF)	Munsell
SEMI-GLOSS		
0190	83.9	7.0Y 9.2/0.2
K175	75.9	5.2Y 8.8/0.9
0161	48.0	1.7Y 7.3/1.5
0109	37.9	6.0Y 6.6/1.0
X114	43.7	1.4GY 7.0/0.3
0182	22.6	1.9B 5.3/0.1
0180	11.4	1.3B 3.9/0.4
K111	5.0	10.0B 2.6/0.1
MATTE		
0790	83.4	4.9Y 9.2/0.2
K775	75.9	5.2Y 8.8/0.9
0761	48.1	2.5Y 7.3/1.5
0709	36.9	5.6Y 6.5/1.0
X714	43.9	3.6GY 7.0/0.4
0782	22.3	9.8G 5.3/0.1
0780	11.1	0.6B 3.9/0.4
K711	5.8	3.3PB 2.8/0.1
ACCENT		
K189	5.9	5.0PB 2.9/1.2
1012	48.1	9.7YR 7.2/6.9
1049	18.0	1.9B 5.0/4.5
1097	26.4	10.1R 5.6/10.2
0115	12.4	3.4G 4.2/4.6
1174	9.1	5.8PB 3.6/5.6
1178	6.8	5.9RP 3.1/2.0
SH17	14.0	5.1R 4.4/11.1

## TRIM

Type	Number	Size	Pieces/ Carton
 12" Jolly	S-1/212J	1/2 x 11-15/16	12

Jolly suitable for wall applications only.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
Mosaic: 1/8"	 Low (V1)

## PERFORMANCE CHARACTERISTICS

	ASTM#	Gloss Result	Matte Result
Water Absorption	C373	< 3.0%	< 3.0%
Breaking Strength	C648	> 250 lbs	> 250 lbs
Scratch Hardness	MOHS	4.0-6.0	8.0
Chemical Resistance	C650	Resistant	Resistant

For additional information on test results, visit us at:  
[daltille.com/information/TestResults](https://daltille.com/information/TestResults).

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at:  
[daltille.com/Factors](https://daltille.com/Factors).



APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓*
Wet & Level – Interior Floor	≥ 0.42	✓*
Shower Floors (Residential or Commercial)	≥ 0.42	✓*
Exterior Floor Applications, including Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓**
Pool Linings	N/A	✓

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltille.com/DCOF](https://daltille.com/DCOF).

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

\* Matte Mosaics Only

† Darker colors may show scratches

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

Note: Matte colors only.



POST-CONSUMER  
RECYCLED MATERIALS



PRE-CONSUMER  
RECYCLED MATERIALS

All or select items within this series meet the requirements for these qualifications. For more information, visit [daltille.com](https://daltille.com).